

BR-3503 Doppler Radar

The BR-3503 is a cost effective 35.5GHz Doppler radar capable to accurately measure the velocity of

BR-3503 General Description

The BR-3503 Doppler radar antenna utilizes the Doppler principle to measure the velocity of moving objects. This radar can be used in a variety of application such as projectile muzzle velocity, in-bore measurement, very short range velocity measurement, etc. It is a great alternative to optical chronographs. The BR-3503 is compact as well as easy to deploy and use. It works at 35.5GHz and provides more than 3 times better resolution than a 10.5GHz (X-Band) radar, and can therefore be used on very small projectile calibers (ex: 1mm spheres). The BR-3503 is particularly well suited for interior ballistic ranges where very short range measurements (down to few meters) are performed. It can also be used outside for short and medium range measurements, depending on projectile caliber.

When used in conjunction with Infinity's junction box and TestCenter Doppler processing software, it provides a powerful tool for velocity analysis of moving objects.

In-bore Measurement

Projectile velocity can be measured inside the gun barrel by using the BR-3503 in combination with a reflector, which is typically a metal plate made out of standard 1/8 inch thick aluminum sheet. Special accessories can be provided to properly align the radar beam and the reflector to achieve optimum results. Typically, in-bore measurement can be performed for 20mm caliber and above.

Performance

The BR-3503 has been designed for short range applications. The following table summarizes the expected range performance for different projectile calibers. Actual performance can vary slightly based on projectile shape and material as well as test conditions.



Caliber	Maximum Range
4.7mm	125m
20mm	530m
25mm	650m
155mm	>1000m

Specifications

Antenna gain	28dBi
Antenna Type	Lens Horn
Beamwidth	4 x 4 deg
Polarization	Circular
Transmitter Output Power	> 0.1 Watt
Transmitter Source	Gunn, CW
Modulation	None
Frequency	35.5GHz (nominal)
Stability	+/-0.1%
Receiver Noise Figure	< 8dB
Radial Velocity Coverage	30 – 3000m/s
Operating Temperature	-20 to 50degC
Supply	115Vac 60Hz 0.3A (North America Model) 230Vac 50Hz 0.15A (European Model)
Dimension (antenna head)	(L) 35.5cm x (OD) 19.0cm
Dimension (power supply)	20cm x 15cm x 6cm
Weight	6.35kg
Approvals	FCC



INFINITY

sales@infinity.com

www.infinity.com